PUSH-ROD AND ROBOTIC CRAWLER CABLES (FOR MARITIME & UNDERWATER INSPECTION)

POWER + VISION + OPTICS + DIGITAL

Application

Underwater inspection of pipelines such as sewer, water, and drainage systems. RS-POWER cables are uniquely designed for the low friction, low wear, plain push distance, and the low ability to withstand high tension/ Top/ Bottom compression loads, high flexibility, low resistance, and corrosion-wear environment.

Push Rod Video Inspection Cable

Tinned Copper Conductor with PVC

Insulation, Mesh Shielded Copper/Mylar with Low Dielectric Constant/ MC Robot

Crawler Cable Armature Low Loss TX Wire Impedance.

Jacket: Abrasion and Water Resistant, Abrasion and Water Resistant, High-strength rating: Push 600 lbs. to 25,000 lbs.

Color: Yellow, Black, Orange, Gray, Blue, Green, Customize/ All water Rod/ UL high abrasion and chemical resistance, low temperature flexibility and superior bending properties for over-molding. We also offer Ruggedness and Reliable for High Communication Video Push Rod Cables.

Push-rod Cables

• Conductor: Tinned Copper Wire

• Insulation: Foam Skin Polyethylene (FCCT), SkiTPE, HDTV ranging from mark 50 AWG to 22 AWG per conductor (Solid and 19/36), Insulated 1 pair designs as well as Fiber optic elements

• Jacket: Polyurethane (PUR) offers over 30 years of Rocker in Underwater Robotics and Remote Vehicles, Abrasion and Water Resistant, high-strength ratings: Push 600 lbs. to 25,000 lbs.

• Color: Yellow, Black, Orange, Gray, Blue, Green, Customize/ All water Rod/ UL high abrasion and chemical resistance, low temperature flexibility and superior bending properties for over-molding. We also offer Ruggedness and Reliable for High Communication Video Push Rod Cables.

Crawler Video Cables

• Conductor: Bare Copper Wire (CCTV, SDTV, HDTV) ranging from mark 50 AWG to 22 AWG per conductor (Solid and 19/36), Insulated 1 pair designs as well as Fiber optic elements

• Jacket: Polyurethane (PUR) offers over 30 years of Rocker in Underwater Robotics and Remote Vehicles, Abrasion and Water Resistant, high-strength ratings: Push 600 lbs. to 25,000 lbs.

• Color: Yellow, Black, Orange, Gray, Blue, Green, Customize/ All water Rod/ UL high abrasion and chemical resistance, low temperature flexibility and superior bending properties for over-molding. We also offer Ruggedness and Reliable for High Communication Video Push Rod Cables.

OUR ADVANTAGES

CABLE SOLUTIONS
Our engineers can design and manufacture cables to meet your specific requirements.

NO FAULTS
We are committed to providing you with the highest quality products and services.

HIGH-LEVEL EXPERIENCE
Our engineers have many years of experience in the design and manufacture of cables.

ENCLOSED PACKAGE
Our cables are packaged in a way that protects them from damage during transportation.

AUTOMATIC RELEASE
We have a fully automated system that can release your cables quickly and easily.

FLEXIBLE CABLE
Our cables are flexible and can be easily bent and twisted.

PUSH-ROD AND ROBOTIC CRAWLER CABLES

PRODUCT MIX

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 9.5 mm.

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 11.0 mm.

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 13.0 mm.

Push Rod Video Inspection Cable
2 Coax + 2 Twisted Pairs + Fiberglass Epoxy Rod
Diameter 13.0 mm.

Push Rod Video Inspection Cable
2 Coax + 2 Twisted Pairs + Fiberglass Epoxy Rod, 4 Core
Diameter 15.0 mm.

Push Rod Video Inspection Cable
14 Core + Coax Diameter 10.0 mm.

Push Rod Video Inspection Cable
7 Core + Coax Diameter 10.0 mm.

Push Rod Video Inspection Cable
12 Core + Coax Diameter 8.5 mm.

CABLES FOR MARITIME AND UNDERWATER TECHNOLOGIES

Underwater technology, especially at great depths, is challenging. ROVs, used for underwater inspection, survey and search work.Require cables with high performance and reliability for efficient and accurate control, providing the required data. Our RS-POWER cables are specially designed and used for Resistivity Operated Valves.to represent the vital connection between the vehicle and the vessel.These products are designed for harsh environments, faster strength member cables, hybrid cables.

We has many years of knowledge and experience manufacturing cables for ROVs and AUVs. Our engineers design and customize umbilicals, video, power and combined service cables, designed to meet the extreme pressures of the deepest ocean environments. Our cables are designed to be flexible, cost-effective engineering solutions to suit your requirements and your budget.

SUBSEA CABLES TYPE

SUBSEA CABLES TYPE
ROV Tether Cable
Umbilical Cable Assembly
Wire umbilical
Push robotic cleaner cable
Neutrally Buoyant Cable
Diver Communication Cable
Underwater Fiber Optic Cable
CCTV Inspection Crawler Robot Cable
Underwater Fiber Optic Cable
Underwater Instrumentation Cable
Underwater Multiconductor Power & Control Cable
Underwater Video Cable
Telecom Sensor Tow Cable
Cable Oceanographic Tow Cable
Push rod Cables
Polyurethane or Polyethylene Jacketed Cables
Steel armored Polyurethane Jacketed Cables
Shift underwater cable/Lockheed Optical
Custom Cable Designs

PUSH-ROD AND ROBOTIC CRAWLER CABLES

DETAIL DISPLAY

LONG DISTANCE DATA TRANSMISSION

Conductors: Stranded Copper Wire, Insulation: Foam Skin Polyethylene (FCCT), Jacket: Polyurethane (PUR) offers over 30 years of Rocker in Underwater Robotics and Remote Vehicles, Abrasion and Water Resistant, high-strength ratings: Push 600 lbs. to 25,000 lbs.

BLOCKED CABLE

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 9.5 mm.

FIBERGLASS EPOXY ROD

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 9.5 mm.

RESILIENT, FLEXIBLE AND MECHANICALLY ROUGHNT ONE SINGLE CABLE WITH NO SPLICES REQUIRED

Underwater ROV cables consist of a combination of power, video, and communication conductors, and are designed to withstand the rigors of underwater environments.

SMALL SIZES, LIGHT WEIGHT, HIGH TENSILE ABRASION EROSION RESISTANT

Push Rod Video Inspection Cable
4 Core, 1 Fiberglass Epoxy Rod
Diameter 9.5 mm.